

Datum: 01.05.2025



(slika je simbolična)

## Ravni navoj. prik. M, G 1/2 , za 6/8 mm, AF 27, PA

Kategorija: [Male connector with male G thread](#)

Šifra: **110776RIE**

### Kratek opis

Straight screw-in fitting, G 1/2 o., for hose 6/8 mm, AF 27, Working pressure max. 10 bar (20°C)/max. 1 bar (60°C), PA  
Manufactured from high impact-resistant, UV-stabilised engineering plastic, extremely resistant to weathering.  
Good chemical resistance to benzine, diesel oil, fuel oil and alkalis. Not suitable for use with acids.

### Tehnične Specifikacije

|                                    |                    |
|------------------------------------|--------------------|
| Narezana matica                    | Polypropylene (PP) |
| Navoj                              | G 1/2              |
| Telo vijačnega priključka          | Polyamide (PA)     |
| Vpenjalni obroč                    | Polypropylene (PP) |
| Max. delovni tlak pri 60 ° C [bar] | 1                  |
| Za cevi [mm]                       | 6/8                |
| Max. delovni tlak pri 20 ° C [bar] | 10                 |
| L2 [mm]                            | 14.0               |
| a/f [mm]                           | 27                 |
| L1 [mm]                            | 47.0               |