

Datum: 02.05.2025



(slika je simbolična)

## [Ravni potisni v pregradni priključek »Metallica«, M28x1.5](#)

Kategorija: [Female bulkhead connectors »metallica«](#)

Šifra: **136780RIE**

### Kratek opis

Straight push-in bulkhead connector »metallica«, M28x1.5, for hose exterior Ø 16 mm, Working pressure -0.98 to 16 bar "

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

### Tehnične Specifikacije

|                               |                            |
|-------------------------------|----------------------------|
| Min. delovna temperatura [°C] | -20                        |
| Min. delovni tlak [bar]       | -0.98                      |
| Material                      | Nickel-plated brass        |
| Navoj                         | M28x1.5                    |
| Priporočena cev               | PA and PU                  |
| Rokav                         | Nickel-plated brass        |
| Serija                        | metallica                  |
| Vpenjalni obroč               | Female bulkhead connectors |
| Max. delovni tlak [bar]       | 16                         |
| Za cevi O.D. [mm]             | 16                         |
| a/f [mm]                      | 36                         |
| L1 [mm]                       | 50.0                       |
| Max. delovna temperatura [°C] | 150                        |