

Datum: 01.05.2025



(slika je simbolična)

## Ravni vtični konektor »klik klak« M24x1, cev ext. Ø 14

Kategorija: [Union](#)

Šifra: **108727RIE**

### Kratek opis

Straight push-in connector »click-clock«, M24x1, for hose exterior Ø 14 mm, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.99               |
| Material                      | Nickel-plated brass |
| Navoj                         | M24x1.0             |
| Priporočena cev               | PA, PU              |
| Rokav                         | Hostaform           |
| Serijska                      | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Za cevi O.D. [mm]             | 14                  |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 45.9                |
| Max. delovna temperatura [°C] | 80                  |