

Datum: 30.04.2025

Davčna št.: SI 56119488

Telefon: 01 500 14 42

E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)

WWW: [www.mail.karchertest.staging.digitalist.si](http://www.mail.karchertest.staging.digitalist.si)



(slika je simbolična)

## Reducerna objemka 240, N.N./N.N.Rp 2Rp 1 1/4

Kategorija: [Socket 240, reducing, female/female](#)

Šifra: **113044RIE**

### Kratek opis

Bushing 240, reducing, IT/IT, Rp 2, Rp 1 1/4, Operating temp. -20°C to 300°C, black malleable cast iron, Hot-dip galvanised

Acc. to DIN EN 10242 (formerly DIN 2950)

The classic - and the most popular - screw fitting series for pipe construction.

These fittings are characterized by their high mechanical strength and surface quality to DIN 2444.

They are completely coated with a layer of pure zinc and are therefore suitable for drinking water

### Tehnične Specifikacije

|                                |                                                     |
|--------------------------------|-----------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                 |
| Material                       | Black malleable iron<br>B350-10, design<br>symbol A |
| Navoj 1                        | Rp 2                                                |
| Navoj 2                        | Rp 1 1/4                                            |
| Površina                       | Hot dip galvanised                                  |
| Standardni navoj               | acc. ISO 7-1                                        |
| Max. temperaturno območje [°C] | 300                                                 |