

Datum: 15.05.2025



(slika je simbolična)

## Reducirni nastavek 241,R 2 Z.N.Rp 1/2 N.N.

Kategorija: [Reducing bush 241, male/female, black](#)

Šifra: **133742RIE**

### Kratek opis

Reducing piece 241, R 2 ET, Rp 1/2 IT black malleable iron fitting, operating temp. -20 °C to 300 °C, ISO 7-1 According to DIN EN 10242 (previously 2950). Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.  
Working minimal temperature = -20 °C, 25 bar.  
Working pressure for temperature range from -20 °C to 120 °C: 25 bar.  
Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

### Tehnične Specifikacije

|                                |                                               |
|--------------------------------|-----------------------------------------------|
| Min. temperaturno območje [°C] | -20                                           |
| Material                       | Black malleable iron B350-10, design symbol A |
| Navoj 1                        | R 2                                           |
| Navoj 2                        | Rp 1/2                                        |
| Površina                       | Black                                         |
| Standardni navoj               | acc. ISO 7-1                                  |
| Max. temperaturno območje [°C] | 300                                           |