

Datum: 01.05.2025



(slika je simbolična)

## Regulator zgoščenega tlaka, hitri priključek za cev 5/3, G 1/8

Kategorija: [Mini pressure regulator, discharge port on thread](#)

Šifra: **107039RIE**

### Kratek opis

Compact pressure regulator, Quick connector for hose 5/3, G 1/8, Control range 0 - 8 bar, Temp. 0 °C to 70 °C, nickel-plated brass

Piston pressure regulator with self-relieving design, hollow bolt and pivoting ring piece. The regulator is connected directly into the consumer (e.g. cylinder, handling equipment, etc.). The working pressure can thus be adapted to the specific application.

### Tehnične Specifikacije

|                                |                                    |
|--------------------------------|------------------------------------|
| Nastavitveni vijak             | Nickel-plated brass                |
| Navoj                          | G 1/8                              |
| Nihajna roka                   | Nickel-plated brass                |
| Notranji deli                  | Brass with a bare metal surface    |
| Tesnilo                        | NBR                                |
| Votli vijak                    | Nickel-plated brass                |
| Zarobljena tesnila             | Polyamide (glass fibre-reinforced) |
| Za cevi [mm]                   | 5 / 3                              |
| Max. krmilno območje [bar]     | 8                                  |
| Max. vhodni tlak [bar]         | 10                                 |
| a/f [mm]                       | 15                                 |
| C [mm]                         | 25.0                               |
| B [mm]                         | 56.0                               |
| Max. temperaturno območje [°C] | 70                                 |