

**Datum:** 01.05.2025

(slika je simbolična)

**Serv. enota 2-delna»FUTURA«PC Vel.1, G 1/4, 0.5-16 Avt.**Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)Šifra: **152368RIE****Kratek opis**

Service unit 2-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 1, G 1/4, Control range 0.5-16 bar, Fully

Two-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

**Tehnične Specifikacije**

|                                |                                              |
|--------------------------------|----------------------------------------------|
| Min. temperaturno območje [°C] | -10                                          |
| Element filtra                 | Cellpor (PE)                                 |
| Membrane                       | NBR                                          |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$               |
| Merjenje pretoka               | bar and pressure drop                        |
|                                | $\Delta_p = 1$ bar                           |
| Navoj                          | G 1/4                                        |
| Odtok kondenzata               | Fully-automatic                              |
| Ohišje                         | PA66 GF60                                    |
| Posoda                         | Polycarbonate container with protective cage |
| Priključni navoj               | Material: Die-cast zinc                      |
| Serijska                       | FUTURA                                       |
| Srednje                        | Compressed air, neutral gases                |
| Tesnilo                        | NBR                                          |
| Vidna kupola                   | PC                                           |
| Min. krmilno območje [bar]     | 0.5                                          |
| Velikost                       | 1                                            |
| Min. vhodni tlak [bar]         | 1.5                                          |
| Rang filtra [µm]               | 5                                            |
| Max. krmilno območje [bar]     | 16                                           |
| Max. vhodni tlak [bar]         | 16                                           |
| Zaslon manometra max. [bar]    | 25                                           |
| Max. temperaturno območje [°C] | 50                                           |
| C [mm]                         | 96.0                                         |
| A [mm]                         | 104.0                                        |
| B [mm]                         | 243.0                                        |
| Pretok [l/min]                 | 1750                                         |