

Datum: 01.05.2025



(slika je simbolična)

**Serv. enota 2-delna»FUTURA«PC Vel.2, G 3/8, 0.5-10 Avt.**Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)Šifra: **152377RIE****Kratek opis**

Service unit 2-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 2, G 3/8, Control range 0.5-10 bar, Fully

Two-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

**Tehnične Specifikacije**

|                                |                                |
|--------------------------------|--------------------------------|
| Min. temperaturno območje [°C] | -10                            |
| Element filtra                 | Cellpor (PE)                   |
| Membrane                       | NBR                            |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$ |
| Merjenje pretoka               | bar and pressure drop          |
|                                | $\Delta_p = 1$ bar             |
| Navoj                          | G 3/8                          |
| Odtok kondenzata               | Fully-automatic                |
| Ohišje                         | PA66 GF60                      |
| Posoda                         | Polycarbonate container        |
| Priključni navoj               | with protective cage           |
| Serijska                       | Material: Die-cast zinc        |
| Srednje                        | FUTURA                         |
| Tesnilo                        | Compressed air, neutral        |
| Vidna kupola                   | gases                          |
| Min. krmilno območje [bar]     | NBR                            |
|                                | PC                             |
| Min. vhodni tlak [bar]         | 0.5                            |
| Velikost                       | 1.5                            |
| Rang filtra [μm]               | 2                              |
| Max. krmilno območje [bar]     | 5                              |
| Max. vhodni tlak [bar]         | 10                             |
| Zaslona manometra max. [bar]   | 16                             |
| Max. temperaturno območje [°C] | 16                             |
| C [mm]                         | 50                             |
| A [mm]                         | 110.0                          |
| B [mm]                         | 126.0                          |
| Pretok [l/min]                 | 273.0                          |
|                                | 3500                           |