

Datum: 01.05.2025



(slika je simbolična)

Serv. enota 2-delna»FUTURA«PCVel.1,G 3/8, 0.5-8Avt.Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)Šifra: **100226RIE****Kratek opis**

Service unit 2-part »FUTURA« with PC container, Protective cage and pressure gauge, Size 1, G 3/8, Control range 0.5-8 bar, Fully

Two-piece service units with excellent flow rates in modern design.

Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$
Merjenje pretoka	bar and pressure drop
	$\Delta_p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Fully-automatic
Ohišje	PA66 GF60
Posoda	Polycarbonate container
Priključni navoj	with protective cage
Serijska	Material: Die-cast zinc
Srednje	FUTURA
Tesnilo	Compressed air, neutral
Vidna kupola	gases
Min. krmilno območje [bar]	NBR
Velikost	PC
Min. vhodni tlak [bar]	0.5
Rang filtra [µm]	1
Max. krmilno območje [bar]	1.5
Zaslon manometra max. [bar]	5
Max. vhodni tlak [bar]	8
Max. temperaturno območje [°C]	10
C [mm]	16
A [mm]	50
B [mm]	96.0
Pretok [l/min]	104.0
	243.0
	1750