

Datum: 02.05.2025



(slika je simbolična)

**Serv. enota 2-delna »G«PC zbir.5 µmVel. 300G 3/8**Kategorija: [Service unit, 2-piece with PC bowl, bowl guard](#)Šifra: **116374RIE****Kratek opis**

Service unit 2-part »G«, PC container, Protective cage, 5 µm, Size 300, G 3/8, Input pressure max. 10 bar, Control range 1.5-9 bar

Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

**Tehnične Specifikacije**

|                                 |                                                                            |
|---------------------------------|----------------------------------------------------------------------------|
| Merjenje pretoka                | At $P_1 = 8$ bar, $P_2 = 6$ bar<br>and pressure drop $\Delta p = 1$<br>bar |
| Navoj                           | G 3/8                                                                      |
| Odtok kondenzata                | Semi-automatic                                                             |
| Ohišje                          | Die-cast aluminium                                                         |
| Posoda                          | Polycarbonate container<br>with protective cage                            |
| Serija                          | G                                                                          |
| Tesnilo                         | NBR                                                                        |
| Vidna kupola                    | Brass/POM                                                                  |
| Vzmet pokrova motorja           | POM                                                                        |
| Min. krmilno območje<br>[bar]   | 1.5                                                                        |
| Rang filtra [µm]                | 5                                                                          |
| Max. krmilno območje<br>[bar]   | 9                                                                          |
| Max. vhodni tlak [bar]          | 10                                                                         |
| Max. sobna temperatura<br>[°C]  | 70                                                                         |
| Max. temperatura medija<br>[°C] | 70                                                                         |
| C [mm]                          | 82.5                                                                       |
| A [mm]                          | 115.0                                                                      |
| D [mm]                          | 143.0                                                                      |
| B [mm]                          | 225.5                                                                      |
| Velikost                        | 300                                                                        |
| Pretok [l/min]                  | 1350                                                                       |