

Datum: 08.05.2025



(slika je simbolična)

Serv. enota 2-delna »GA« PC zbir.5 µm, Vel. 400, G 3/8Kategorija: [Service unit, 2-piece with PC bowl, bowl guard](#)Šifra: **178494RIE****Kratek opis**

Service unit 2-part »GA«, PC container, Protective cage, 5 µm, Size 400, G3/8, Input pressure max. 10 bar, Control range 1.5-9 bar

Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-5
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/8
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast aluminium
Posoda	Polycarbonate container with protective cage
Serija	GA
Tesnilo	NBR
Vidna kupola	Brass/POM
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	1.5
Rang filtra [µm]	5
Max. krmilno območje [bar]	9
Max. vhodni tlak [bar]	10
Max. temperaturno območje [°C]	70
C [mm]	108.0
A [mm]	164.0
D [mm]	177.5
B [mm]	285.5
Velikost	400
Pretok [l/min]	3500