

Datum: 30.04.2025



(slika je simbolična)

Serv. enota 2-delna »multifix«Kov. pos.Vel. 3G 1/2

Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)Šifra: **100578RIE**

Kratek opis

Service unit 2-part »multifix«, Metal container, Viewing tube, Size 3, G 1/2, Input pressure max. 20 bar, Control range 0.5-10 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1/2
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Metal container with viewing tube
Serija	multifix
Tesnilo	NBR
Vidna kupola	Zinc-glass-NBR
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
Velikost	3
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
DN	15
Zaslona manometra max. [bar]	16
Max. vhodni tlak [bar]	20
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	99.0
A [mm]	134.8
D [mm]	149.2
B [mm]	248.2
Pretok [l/min]	5800