

Datum: 30.04.2025



(slika je simbolična)

Serv. enota 2-delna »multifix« z PC zbir.Vel. 3G 3/4

Kategorija: [Service unit, 2-piece with polycarbonate bowl](#)Šifra: **100569RIE**

Kratek opis

Service unit 2-part »multifix« with polycarbonate container, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc
Posoda	Polycarbonate container
Serija	multifix
Tesnilo	NBR
Vidna kupola	PA
Vzmet pokrova motorja	POM-brass
Min. krmilno območje [bar]	0.5
Velikost	3
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
DN	20
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
C [mm]	99.0
A [mm]	134.8
D [mm]	147.3
B [mm]	246.3
Pretok [l/min]	5800