

Datum: 01.05.2025



(slika je simbolična)

## **Serv. enota 2-delna »multifix«Zašč. kletkaVel. 3G 3/4**

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)

Šifra: **100574RIE**

### **Kratek opis**

Service unit 2-part »multifix«, PC container, Protective cage, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5-10 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

### **Tehnične Specifikacije**

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 3/4                                                                   |
| Odtok kondenzata             | Semi-automatic                                                          |
| Ohišje                       | Die-cast zinc                                                           |
| Posoda                       | Polycarbonate container with protective cage                            |
| Serija                       | multifix                                                                |
| Tesnilo                      | NBR                                                                     |
| Vidna kupola                 | PA                                                                      |
| Vzmet pokrova motorja        | POM-brass                                                               |
| Min. krmilno območje [bar]   | 0.5                                                                     |
| Velikost                     | 3                                                                       |
| Rang filtra [ $\mu$ m]       | 5                                                                       |
| Max. krmilno območje [bar]   | 10                                                                      |
| Max. vhodni tlak [bar]       | 16                                                                      |
| Zaslon manometra max. [bar]  | 16                                                                      |
| DN                           | 20                                                                      |
| Max. sobna temperatura [°C]  | 60                                                                      |
| Max. temperatura medija [°C] | 60                                                                      |
| C [mm]                       | 99.0                                                                    |
| A [mm]                       | 134.8                                                                   |
| D [mm]                       | 147.3                                                                   |
| B [mm]                       | 246.3                                                                   |
| Pretok [l/min]               | 5800                                                                    |