

Datum: 10.05.2025



(slika je simbolična)

**Serv. enota 2-delna »variobloc«Kov. pos.Vel.1,G 1/4**Kategorija: [Service unit, 2-piece with metal bowl, sight glass](#)Šifra: **125345RIE****Kratek opis**

Service unit 2-part »variobloc«, Metal container incl. viewing tube and metal drip cap, Size 1, G 1/4, Input pressure max. 20 bar

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

**Tehnične Specifikacije**

|                              |                                                                       |
|------------------------------|-----------------------------------------------------------------------|
| Membrane                     | NBR                                                                   |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1/4                                                                 |
| Odtok kondenzata             | Manual                                                                |
| Ohišje                       | Die-cast zinc                                                         |
| Posoda                       | Metal container with viewing tube                                     |
| Serijska                     | variobloc                                                             |
| Tesnilo                      | NBR                                                                   |
| Vidna kupola                 | PA                                                                    |
| Vzmet pokrova motorja        | POM                                                                   |
| Min. krmilno območje [bar]   | 0.5                                                                   |
| Velikost                     | 1                                                                     |
| Max. krmilno območje [bar]   | 10                                                                    |
| Zaslon manometra max. [bar]  | 10                                                                    |
| Max. vhodni tlak [bar]       | 20                                                                    |
| Rang filtra [ $\mu$ m]       | 40                                                                    |
| C [mm]                       | 68.0                                                                  |
| Max. sobna temperatura [°C]  | 80                                                                    |
| Max. temperatura medija [°C] | 80                                                                    |
| A [mm]                       | 96.0                                                                  |
| B [mm]                       | 203.0                                                                 |
| Pretok [l/min]               | 1500                                                                  |