

Datum: 06.05.2025



(slika je simbolična)

Serv. enota 2-delna »variobloc«Zašč. kletkaVel. 2G 1Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)Šifra: **124873RIE****Kratek opis**

Service unit 2-part »variobloc«, PC container and protective cage, Size 2, G 1, Input pressure max. 16 bar, Temp. max. 50 °C

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

Tehnične Specifikacije

Membrane	NBR
Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Navoj	G 1
Odtok kondenzata	Manual
Ohišje	Die-cast zinc Polycarbonate container with protective cage variobloc
Posoda	NBR
Serija	PA
Tesnilo	POM
Vidna kupola	0.5
Vzmet pokrova motorja	2
Min. krmilno območje [bar]	10
Velikost	10
Max. krmilno območje [bar]	16
Zaslon manometra max. [bar]	40
Max. vhodni tlak [bar]	50
Rang filtra [μ m]	50
Max. sobna temperatura [°C]	50
Max. temperatura medija [°C]	98.0
C [mm]	194.0
A [mm]	273.0
B [mm]	5000
Pretok [l/min]	