

Datum: 06.05.2025



(slika je simbolična)

## Serv. enota 2-delna »variobloc« Zašč. kletka Vel.2, G 1/2

Kategorija: [Service unit, 2-piece with PC bowl and bowl guard](#)Šifra: **124868RIE**

### Kratek opis

Service unit 2-part »variobloc«, PC container and protective cage, Size 2, G 1/2, Input pressure max. 16 bar, Temp. max. 50 °C

Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Approved series in modern industrial design, with the following key benefits:

- Simple handling
- Convenient modular assembly thanks to innovative fasteners
- Excellent flow values

### Tehnične Specifikacije

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Membrane                     | NBR                                                                     |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar   |
| Navoj                        | G 1/2                                                                   |
| Odtok kondenzata             | Manual                                                                  |
| Ohišje                       | Die-cast zinc<br>Polycarbonate container with protective cage variobloc |
| Posoda                       | NBR                                                                     |
| Serija                       | PA                                                                      |
| Tesnilo                      | POM                                                                     |
| Vidna kupola                 | 0.5                                                                     |
| Vzmet pokrova motorja        | 2                                                                       |
| Min. krmilno območje [bar]   | 10                                                                      |
| Velikost                     | 10                                                                      |
| Max. krmilno območje [bar]   | 16                                                                      |
| Zaslon manometra max. [bar]  | 40                                                                      |
| Max. vhodni tlak [bar]       | 50                                                                      |
| Rang filtra [ $\mu$ m]       | 50                                                                      |
| Max. sobna temperatura [°C]  | 50                                                                      |
| Max. temperatura medija [°C] | 98.0                                                                    |
| C [mm]                       | 140.0                                                                   |
| A [mm]                       | 273.0                                                                   |
| B [mm]                       | 3400                                                                    |
| Pretok [l/min]               |                                                                         |