

Datum: 30.04.2025



(slika je simbolična)

## Serv. enota 3-delna »Stinard«Kov. pos.Vel.1,G 1/4

Kategorija: [Service unit, 3-piece with metal bowl](#)Šifra: **101080RIE**

### Kratek opis

Service unit 3-part »Standard«, Metal container, metal drip cap, Size 1, G 1/4, Input press. max. 25 bar, Control range 0.5-16 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar |
| Navoj                        | G 1/4                                                                |
| Odtok kondenzata             | Manuel                                                               |
| Ohišje                       | Die-cast zinc / aluminium, painted silver                            |
| Posoda                       | Metal container                                                      |
| Serijska                     | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Vidna kupola                 | Zinc-glass-NBR                                                       |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 1                                                                    |
| Rang filtra [ $\mu$ m]       | 5                                                                    |
| DN                           | 6                                                                    |
| Max. krmilno območje [bar]   | 16                                                                   |
| Max. vhodni tlak [bar]       | 25                                                                   |
| Zaslon manometra max. [bar]  | 25                                                                   |
| Manometer $\varnothing$ [mm] | 50                                                                   |
| C [mm]                       | 51.0                                                                 |
| Max. sobna temperatura [°C]  | 60                                                                   |
| Max. temperatura medija [°C] | 60                                                                   |
| A [mm]                       | 172.0                                                                |
| B [mm]                       | 184.5                                                                |
| Pretok [l/min]               | 600                                                                  |