

Datum: 06.05.2025



(slika je simbolična)

Serv. enota 3-delna »Stinard«Zašč. kletkaVel. 3G 3/4Kategorija: [Service unit, 3-piece with PC bowl and bowl guard](#)Šifra: **101076RIE****Kratek opis**

Service unit 3-part »Standard«, PC container, protective cage, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5-10 bar

Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 3/4
Odtok kondenzata	Semi-automatic
Ohišje	Die-cast zinc / aluminium, painted silver
Posoda	Polycarbonate container with protective cage
Serijska	Standard
Tesnilo	NBR
Vidna kupola	PA
Min. krmilno območje [bar]	0.5
Velikost	3
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslona manometra max. [bar]	16
DN	20
C [mm]	58.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Manometer Ø [mm]	63
B [mm]	227.9
A [mm]	302.0
Pretok [l/min]	3200