

Datum: 01.05.2025



(slika je simbolična)

Servisna enota »ENO« s tlačnim stikalom, G 1/2

Kategorija: [Service unit, »ONE« series, with pressure switch](#)Šifra: **101127RIE**

Kratek opis

Service unit »ONE« with pressure switch, G 1/2, Input pressure max. 10 bar, Control range 0.5 - 8 bar, Temp. -10 °C to 50 °C

Multifunctional service unit with 6 or 7 functions in a single device:

3/2-way valve (manually operated), filter with automatic drain valve, air ports, pressure regulator, pressure gauge, soft start valve and optional pressure switch

This combination of extremely good flow rates and a wide range of functions integrated in a single, compact unit saves valuable space and is unmatched by any similar product available in the market!

Soft starting independently of the load and easy replacement of the filter cartridge under pressure are just two of the other outstanding features of this amazing device.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
IP zaščita	IP 65
Merjenje pretoka	At $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Serijska	ONE
Srednje	Pneumatics
Min. krmilno območje [bar]	0.5
Max. krmilno območje [bar]	8
Max. vhodni tlak [bar]	10
Rang filtra [µm]	20
Operativna napetost	24 V DC (for valves and pressure switch)
C [mm]	35.0
Max. temperaturno območje [°C]	50
B [mm]	144.0
A [mm]	165.5
Pretok [l/min]	4000