

**Datum:** 30.04.2025

(slika je simbolična)

## **Servisna enota VARNOSTNA »FUTURA«, Velikost 2, G 1/2**

Kategorija: [SAFETY service unit set](#)Šifra: **100258RIE**

### **Kratek opis**

Service station SAFETY »FUTURA«, Ball valve - start-up valve - filter regulator, Size 2, G 1/2, Input pressure 2.5 - 16 bar  
These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

### **Tehnične Specifikacije**

|                                |                                |
|--------------------------------|--------------------------------|
| Min. temperaturno območje [°C] | -10                            |
| Element filtra                 | Cellpor (PE)                   |
| Membrane                       | NBR                            |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$ |
| Merjenje pretoka               | bar and pressure drop          |
|                                | $\Delta p = 1$ bar             |
| Navoj                          | G 1/2                          |
| Odtok kondenzata               | Fully-automatic                |
| Odzračevalni vtič              | Silencer (ball valve)          |
| Ohišje                         | PA66 GF60                      |
| Priključni navoj               | Material: Die-cast zinc        |
| Serijska                       | FUTURA                         |
| Srednje                        | Compressed air, neutral gases  |
| Tesnilo                        | NBR                            |
| Velikost                       | 2                              |
| Min. krmilno območje [bar]     | 2.5                            |
| Min. vhodni tlak [bar]         | 2.5                            |
| Rang filtra [µm]               | 5                              |
| Max. krmilno območje [bar]     | 8                              |
| Zaslon manometra max. [bar]    | 10                             |
| Max. vhodni tlak [bar]         | 16                             |
| Max. temperaturno območje [°C] | 50                             |
| C [mm]                         | 110.0                          |
| A [mm]                         | 189.0                          |
| B [mm]                         | 273.0                          |
| Pretok [l/min]                 | 4500                           |