

Datum: 10.05.2025



(slika je simbolična)

## Servisna enota VARNOSTNA »FUTURA«, Velikost 4, G 1

Kategorija: [SAFETY service unit set](#)Šifra: **100272RIE**

### Kratek opis

Service station SAFETY »FUTURA«, Ball valve - start-up valve - 2-part service unit, Size 4, G 1, Input pressure 2.5 - 16 bar  
These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

### Tehnične Specifikacije

|                                |                                                                         |
|--------------------------------|-------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                                                     |
| Element filtra                 | Cellpor (PE)                                                            |
| Membrane                       | NBR                                                                     |
|                                | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Merjenje pretoka               | G 1                                                                     |
| Navoj                          | Fully-automatic                                                         |
| Odtok kondenzata               | Silencer (ball valve)                                                   |
| Odzračevalni vtič              | PA66 GF60                                                               |
| Ohišje                         | Yes                                                                     |
| Poraba zraka                   | Material: Die-cast zinc                                                 |
| Priključni navoj               | FUTURA                                                                  |
| Serijska                       | Compressed air, neutral gases                                           |
| Srednje                        | NBR                                                                     |
| Tesnilo                        | 1.5 l/min (depending on secondary pressure)                             |
| Max. notranja poraba zraka     | 2.5                                                                     |
| Min. krmilno območje [bar]     | 2.5                                                                     |
| Min. vhodni tlak [bar]         | 2.5                                                                     |
| Velikost                       | 4                                                                       |
| Rang filtra [µm]               | 5                                                                       |
| Max. krmilno območje [bar]     | 8                                                                       |
| Zaslon manometra max. [bar]    | 10                                                                      |
| Max. vhodni tlak [bar]         | 16                                                                      |
| Max. temperaturno območje [°C] | 50                                                                      |
| C [mm]                         | 137.0                                                                   |
| A [mm]                         | 340.0                                                                   |
| B [mm]                         | 343.0                                                                   |
| Pretok [l/min]                 | 10000                                                                   |