

Datum: 01.05.2025

(slika je simbolična)

Servisna enota VARNOSTNA »multifix«, Velikost 3, G 1/2

Kategorija: [SAFETY service unit set](#)Šifra: **100597RIE**

Kratek opis

Service station SAFETY »multifix«, Ball valve - start-up valve - pressure regulator, Size 3, G 1/2, Input pressure 2 - 16 bar
These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Tehnične Specifikacije

Element filtra	Cellpor (PE)
Membrane	NBR
Merjenje pretoka	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1/2
Odzračevalni vtič	Silencer (ball valve)
Ohišje	Die-cast zinc
Serijska	multifix
Srednje	Compressed air
Tesnilo	NBR
Vzmet pokrova motorja	POM
Min. krmilno območje [bar]	2
Min. vhodni tlak [bar]	2
Velikost	3
Rang filtra [μ m]	5
Max. krmilno območje [bar]	10
Max. vhodni tlak [bar]	16
Zaslon manometra max. [bar]	16
Max. temperaturno območje [$^{\circ}$ C]	60
C [mm]	122.0
A [mm]	189.0
B [mm]	200.8
Pretok [l/min]	4000