

Datum: 11.05.2025



(slika je simbolična)

## [sesalno cev / tlaka, gume, SBR, cev Ø 30x19, rola 40 m](#)

Kategorija: [Suction and discharge hoses »Heduflex®« 40 m reels](#)

Šifra: **113927RIE**

### Kratek opis

Suction / pressure hose, Rubber, SBR, Temperature -30 °C to 80 °C, Vacuum 0.8 bar, PN max. 10 bar, Hose Ø 30x19, Roll of 40 m

Rubber hose with spiral steel wire embedded in the wall  
Suitable for process water, liquid manure or weak acids and alkaline solutions

Extremely flexible and non-toxic.

**IMPORTANT: These hoses are shipped from our distribution centre in the Netherlands using a forwarding agent.**

### Tehnične Specifikacije

|                                |                                |
|--------------------------------|--------------------------------|
| Min. temperaturno območje [°C] | -30                            |
| Zračnico                       | SBR, black, smooth             |
| Zunanji pokrov                 | SBR, black, patterned material |
| Vakuum [bar]                   | 0.8                            |
| Max. obratovalni tlak [bar]    | 10                             |
| I.D. cevi [mm]                 | 19                             |
| O.D. cevi [mm]                 | 30                             |
| Razpočni tlak [bar]            | 30                             |
| Dolžina koluta [m]             | 40                             |
| Max. temperaturno območje [°C] | 80                             |
| Min. polmer upogibanja [mm]    | 95                             |