

Datum: 02.05.2025



(slika je simbolična)

## Spir. cev , standard, PU, cevi Ø 8x5, dolžina 6,0 m

Kategorija: [Spiral hose coupling kit quick disconnect coupling](#)

Šifra: **158175RIE**

### Kratek opis

Spiral hose coupling set, Standard coupling I.D. 7.2, PU, Hose Ø 8x5, PN at 23 °C max. 12 bar, Length 6.0 m  
These exceptionally elastic polyurethane hoses boast a recoil force similar to that of conventional polyamide spiral hose, but with less tendency to loop and significantly better resistance to abrasion.  
There is consequently less danger of scratching coated or sensitive surfaces.  
The hose is extremely flexible and non-kinking.  
Not suitable for direct attachment to pulsating tools.  
We recommend using our vibration dampers, according to ISO 6150 § 7.1.

### Tehnične Specifikacije

|                                        |     |
|----------------------------------------|-----|
| Min. delovna temperatura [°C]          | -20 |
| Storitev dolžina max. [m]              | 6.0 |
| Velikost cevi [mm]                     | 8x5 |
| Max. obratovalni tlak pri 23 ° C [bar] | 12  |
| O.D. tuljave [mm]                      | 42  |
| Max. delovna temperatura [°C]          | 60  |
| Število tuljav                         | 64  |