

Datum: 02.05.2025



(slika je simbolična)

stand. cilinderdelujoč v dveh smerehbat Ø 40hod 300G 1/4Kategorija: [Standard cylinders - AirSentials](#)Šifra: **114663RIE****Kratek opis**

Standard cylinder »SE« ISO 15552, double-acting, Piston Ø 40, Stroke 300, G 1/4, Working pressure 1 - 10 bar, Temp. -20°C to 70°C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning. The magnetic switches are mounted in T-slots on three sides of the body.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Cushioning	cushioned
ET batnice	M12x1.25
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Aluminium jacket with integrated T-slots
Povezava	G 1/4
Serijska	SE series
Standard	acc. to ISO 15552
Tesnilo	NBR (O-rings)
Tesnilo batnice	TPU (thermoplastic polyurethane)
Min. delovni tlak [bar]	1
Max. delovni tlak [bar]	10
Batnica Ø [mm]	16
Bat Ø [mm]	40
Max. temperaturno območje [°C]	70
Stroke [mm]	300