

Datum: 02.05.2025



(slika je simbolična)

stand. cilinderdelujoč v dveh smerehbat Ø 50, hod 160, G 1/4

Kategorija: [Standard cylinders »SAI« Series](#)
Šifra: **170614RIE**

Kratek opis

Standard cylinder SAI, ISO 15552, double-acting, Piston Ø 50, Stroke 160, G 1/4, Working pressure 1.5-10 bar, Temp. -20°C to 70°C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.

The magnetic switches are mounted in T-slots on two sides of the body.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Bat	Aluminium
Batnica	Steel, thick-chromed
Cushioning	cushioned
ET batnice	M16x1.5
Ffunkcija	double-acting
Gewinde Kolbenstange	male piston rod
Magnet	with magnet
Ovoj	Aluminium jacket with integrated T-slots
Povezava	G 1/4
Standard	acc. to ISO 15552
Tesnilo	NBR (O-rings)
Tesnilo batnice	TPU (thermoplastic polyurethane)
Min. delovni tlak [bar]	1.5
Max. delovni tlak [bar]	10
Batnica Ø [mm]	20
Bat Ø [mm]	50
Max. temperaturno območje [°C]	70
Stroke [mm]	160