

Datum: 02.05.2025



(slika je simbolična)

**stand. cilinderdelujoč v dveh smerehbat Ø 80hod 125G 3/8**Kategorija: [Standard cylinders - AirSentials](#)Šifra: **114719RIE****Kratek opis**

Standard cylinder »SE« ISO 15552, double-acting, Piston Ø 80, Stroke 125, G 3/8, Working pressure 1 - 10 bar, Temp. -20°C to 70°C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning. The magnetic switches are mounted in T-slots on three sides of the body.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

**Tehnične Specifikacije**

|                                |                                          |
|--------------------------------|------------------------------------------|
| Min. temperaturno območje [°C] | -20                                      |
| Bat                            | Aluminium                                |
| Batnica                        | Steel, thick-chromed                     |
| Cushioning                     | cushioned                                |
| ET batnice                     | M20x1.5                                  |
| Ffunkcija                      | double-acting                            |
| Gewinde Kolbenstange           | male piston rod                          |
| Magnet                         | with magnet                              |
| Ovoj                           | Aluminium jacket with integrated T-slots |
| Povezava                       | G 3/8                                    |
| Serija                         | SE series                                |
| Standard                       | acc. to ISO 15552                        |
| Tesnilo                        | NBR (O-rings)                            |
| Tesnilo batnice                | TPU (thermoplastic polyurethane)         |
| Min. delovni tlak [bar]        | 1                                        |
| Max. delovni tlak [bar]        | 10                                       |
| Batnica Ø [mm]                 | 25                                       |
| Max. temperaturno območje [°C] | 70                                       |
| Bat Ø [mm]                     | 80                                       |
| Stroke [mm]                    | 125                                      |