

Datum: 02.05.2025



(slika je simbolična)

Standardni manometer, CrNi jeklo, G 1/4, 0 - 2.5 bar, Ø 50

Kategorija: [Pressure gauge, CrNi steel, standard, conn. rear](#)

Šifra: **102441RIE**

Kratek opis

Standard pressure gauge CrNi steel design, Connection, rear, centric, G 1/4, Goods class 2.5, Measurement range 0 - 2.5 bar, Ø 50

Bourdon-tube pressure gauge (standard model) manufactured entirely from CrNi steel, economical and reliable.

Suitable for gaseous or liquid, corrosive and crystallising media which do not have high viscosity, also in corrosive atmosphere. Clean dry air applications, machinery and industrial plant engineering in general.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-40
Min. temperatura medija [°C]	-40
Material	CrNi steel
Material Prozessanschluss	CrNi steel
Položaj povezave	rear, central
Povezava	G 1/4
Prednje steklo	Polycarbonate
Stopnja rasti na območju skale - bar [bar]	0.1
Merilno območje max. bar	2.5
Razred točnosti	2.5
Merilno območje max. psi	36
Premjer [mm]	50
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	100
Vrsta	131.11