

Datum: 02.05.2025



(slika je simbolična)

Standardni manometer, priklp spodaj, G 1/2, -1 / +5 bar, Ø 100

Kategorija: [Standard pressure gauge, conn. radial on bottom](#)Šifra: **101966RIE**

Kratek opis

Standard pressure gauge, Single scale bar, Connection radial bottom, G 1/2, Goods class 1.6, Measurement range -1 / +5 bar, Ø 100

Bourdon-tube pressure gauge in standard design. Suitable for gaseous or liquid media which do not corrode copper alloy, do not have high viscosity and do not crystallise.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Merilno območje min. bar	-1
Material Prozessanschluss	Copper alloy
Merilni element	Copper alloy
Ohišje	Plastic
Položaj povezave	radial on bottom
Povezava	G 1/2
Prednje steklo	Transparent plastic
Premikanje	Copper alloy
Referenčni kazalnik	-
Spodnja/Zgornja meja območja	Vacuum/Positive pressure
Stopnja rasti na območju skale - bar [bar]	0.1
Razred točnosti	1.6
Merilno območje max. bar	5
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
Premier [mm]	100
Vrsta	111.10