

Datum: 01.05.2025



## Standardni manometer, priklop zadaj, G 1/4, 0 - 16 bar, Ø 50

(slika je simbolična)

Kategorija: [Standard pressure gauges, sheet steel, rear](#)

Šifra: **101827RIE**

### Kratek opis

Standard pressure gauge, Single scale bar, Connection, rear, centric, G 1/4, Goods class 1.6, Measurement range 0 - 16 bar, Ø 50

Bourdon-tube pressure gauge in standard design.

Suitable for gaseous or liquid media which do not corrode copper alloy,

do not have high viscosity and do not crystallise.

### Tehnične Specifikacije

|                                            |                     |
|--------------------------------------------|---------------------|
| Min. sobna temperatura [°C]                | -20                 |
| Min. temperatura medija [°C]               | -20                 |
| Material Prozessanschluss                  | Copper alloy        |
| Merilni element                            | Copper alloy        |
| Ohišje                                     | Sheet steel         |
| Položaj povezave                           | rear, central       |
| Povezava                                   | G 1/4               |
| Prednje steklo                             | Transparent plastic |
| Premikanje                                 | Copper alloy        |
| Spodnja/Zgornja meja območja               | Positive pressure   |
| Stopnja rasti na območju skale - bar [bar] | 0.5                 |
| Razred točnosti                            | 1.6                 |
| Merilno območje max. bar                   | 16                  |
| Premier [mm]                               | 50                  |
| Max. sobna temperatura [°C]                | 60                  |
| Max. temperatura medija [°C]               | 60                  |
| Vrsta                                      | 111.12              |