

Datum: 05.05.2025



(slika je simbolična)

Stenski priključki hN.N.rih spoj s priključnicami I.D. 7.2

Kategorija: [Distributor for wall mountable with coupling DN7.2](#)

Šifra: **107272RIE**

Kratek opis

Distributor for wall mounting with quick-connect couplings I.D. 7.2, Bright brass, G 1/2 IT, Operating pressure 0 - 35 bar 1, 2 or 3-way distributor pieces made of brass with a bare metal surface, pre-assembled with quick disconnect coupling DN 7.2.

Available with threaded connection inside or outside or nipple for adaptation into an existing quick disconnect coupling DN 7.2 to DN 7.8.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Ohišje	Brass with a bare metal surface
Povezava	G 1/2 IT
Spojke	DN 7.2, brass with a bare metal surface, G 1/2 ET
Tesnilo	Industrial adhesives, medium strength
Varovaka	Industrial adhesives, medium strength
Sestava distributerja	5 x G 1/2 outlets
Max. obratovalni tlak [bar]	35
Višina [mm]	57.0
Max. sobna temperatura [°C]	100
Max. temperatura medija [°C]	100
Premer [mm]	113.0