

Datum: 01.05.2025



(slika je simbolična)

T-kos 130, N.N./N.N./N.N.Rp 2T-kos Rp 1/2

Kategorija: [Tee 130, reducing, female/female/female, black](#)

Šifra: **133689RIE**

Kratek opis

T-piece 130, IT/IT/IT, Rp 2, T-branch reducing Rp 1/2, black malleable iron fitting, Operating temp. -20 °C to 300 °C, ISO 7-1

According to DIN EN 10242 (previously 2950).

Malleable iron cast fittings in black steel, non-galvanized, is the classic fitting series in connection series in piping construction. Our malleable iron cast fittings are characterized by high mechanical strength and standardized fitting technology.

Working minimal temperature = -20 °C, 25 bar.

Working pressure for temperature range from -20 °C to 120 °C: 25 bar.

Working pressure for temperature range from 120 °C to 300 °C: 20-25 bar.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Material	Black malleable iron B350-10, design symbol A
Navoj 1	Rp 2
Navoj 2 Zmanjšana razvejanost	Rp 1/2
Navoj 3	Rp 2
Površina	Black
Standardni navoj	acc. ISO 7-1
Max. temperaturno območje [°C]	300