

Datum: 02.05.2025



(slika je simbolična)

Temperaturna sklopka DN 9, navoj 13 mm, Medenina, cevFi cevi ravno

Kategorija: [Temp. control coupl. DN 9, without shut-off valve](#)

Šifra: **107956RIE**

Kratek opis

Tempered coupling DN 9, Taps 13 mm, Brass, Hose sleeve straight, Operating pressure max. 15 bar, Med./ambient temp. -20°C to 160°C
Compatible with HASCO Z 8 system.
For temperature control applications involving hot or cold water or heat transfer oil.
Optionally with free passage, one or both sides sealing.
Female-threaded couplings and plugs with female-threaded PTFE seal.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Krogla	Stainless steel
Material	Brass 2.0401
Pritrdilni obroč	Stainless steel
Srednje	Air, water, oil, vacuum
Tesnilo	FPM (PTFE coated)
Tip stebelnih cevi	straight
Vzmet	Stainless steel
Priključek za cev [mm]	13
Max. obratovalni tlak [bar]	15
Dolžina [mm]	61.5
Max. sobna temperatura [°C]	160
Max. temperatura medija [°C]	160