

Datum: 10.05.2025



(slika je simbolična)

## Temperaturna sklopka DN 9, zunanji navoj, Medenina, G 3/8 ravno

Kategorija: [Temp. control coupl. DN 9, without shut-off valve](#)

Šifra: **107967RIE**

### Kratek opis

Tempered coupling DN 9, Exterior thread, Brass 2.0401, G 3/8 straight, Operating pressure max. 15 bar, Temp. -20 °C to 160 °C

Compatible with HASCO Z 8 system.

For temperature control applications involving hot or cold water or heat transfer oil.

Optionally with free passage, one or both sides sealing.

Female-threaded couplings and plugs with female-threaded PTFE seal.

### Tehnične Specifikacije

|                              |                         |
|------------------------------|-------------------------|
| Min. sobna temperatura [°C]  | -20                     |
| Min. temperatura medija [°C] | -20                     |
| Krogla                       | Stainless steel         |
| Material                     | Brass 2.0401            |
| Priključni navoj             | G 3/8 straight          |
| Pritrdilni obroč             | Stainless steel         |
| Srednje                      | Air, water, oil, vacuum |
| Tesnilo                      | FPM (PTFE coated)       |
| Vzmet                        | Stainless steel         |
| Max. obratovalni tlak [bar]  | 15                      |
| a/f [mm]                     | 22                      |
| Dolžina [mm]                 | 53.5                    |
| Max. sobna temperatura [°C]  | 160                     |
| Max. temperatura medija [°C] | 160                     |