

Datum: 01.05.2025



(slika je simbolična)

## Tesnilno - zaporni ventil, nerjavno jeklo 1.4401/1.4408, G 2

Kategorija: [Female thread gate valves stainless steel](#)

Šifra: **103788RIE**

### Kratek opis

Bushing - locking pusher, Stainless steel 1.4401/1.4408,  
Medium / ambient temperature max. 160 °C, G 2, DN 50, PN  
max. 14 bar

### Tehnične Specifikacije

|                               |                                    |
|-------------------------------|------------------------------------|
| Min. delovna temperatura [°C] | -10                                |
| Kolo                          | Aluminium                          |
| Navoj                         | G 2                                |
| Notranji deli                 | Stainless steel<br>1.4401 / 1.4408 |
| Ohišje                        | Stainless steel<br>1.4401 / 1.4408 |
| Tesnilo                       | PTFE                               |
| Max. obratovalni tlak [bar]   | 14                                 |
| DN                            | 50                                 |
| Max. delovna temperatura [°C] | 80                                 |
| L [mm]                        | 95.0                               |
| A [mm]                        | 100.0                              |
| Max. sobna temperatura [°C]   | 160                                |
| Max. temperatura medija [°C]  | 160                                |
| B [mm]                        | 170.0                              |