

Datum: 30.04.2025



(slika je simbolična)

Throttle check valve, discharge, G 3/8, plug-in connector 8

Kategorija: [Unidirectional flow control valve](#)

Šifra: **116833RIE**

Kratek opis

Throttle check valve, discharge (C), knurled screw, G 3/8, plug-in 8, rotating, 0 to 10 bar, -20 °C to 80 °C, nickel-plated brass

For throttling flow rates and regulating the piston speed of cylinders. Small dimensions, ideal for tight spaces. To be screwed directly into the valve or cylinder. The set flow rate can be locked via the lock nut in the version with knurled screw. The variants in banjo bolt construction can be rotated during assembly and are fixed after tightening. The variants with plug-in connector, rotated can also be rotated freely after assembly. The seals and lubricants used are silicone-free.

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Design	rotating
Ffunkcija	Discharge throttle (C)
Navoj	G 3/8
Silicone-free	Yes
Telo	Nickel-plated brass
Tesnilo	NBR
Vrsta povezave	Plug-in connector
Za cevi [mm]	8
Max. obratovalni tlak [bar]	10
a/f [mm]	14
C [mm]	26.5
B [mm]	63.5
Max. temperaturno območje [°C]	80