

Datum: 02.05.2025



(slika je simbolična)

## Tlačni regulator »Stinard«, Velikost 4, G 1 1/2, 0.5 - 16 bar

Kategorija: [Pressure regulators](#)

Šifra: **100830RIE**

### Kratek opis

Pressure regulator »Standard«, Size 4, G 1 1/2, Input pressure max. 25 bar, Medium temp. max. 60 °C, Control range 0.5 - 16 bar  
Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design.

### Tehnične Specifikacije

|                              |                                                                      |
|------------------------------|----------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 1 1/2                                                              |
| Ohišje                       | Die-cast zinc, painted silver                                        |
| Serija                       | Standard                                                             |
| Tesnilo                      | NBR                                                                  |
| Min. krmilno območje [bar]   | 0.5                                                                  |
| Velikost                     | 4                                                                    |
| Max. krmilno območje [bar]   | 16                                                                   |
| Max. vhodni tlak [bar]       | 25                                                                   |
| Zaslon manometra max. [bar]  | 25                                                                   |
| DN                           | 35                                                                   |
| C [mm]                       | 52.0                                                                 |
| Max. temperatura medija [°C] | 60                                                                   |
| Max. sobna temperatura [°C]  | 80                                                                   |
| A [mm]                       | 125.0                                                                |
| D [mm]                       | 200.5                                                                |
| B [mm]                       | 252.5                                                                |
| Pretok [l/min]               | 16500                                                                |