

Datum: 11.05.2025



(slika je simbolična)

Tlačno stikalo, specialna zlitina, G 1/4, 0.2 - 2 bar

Kategorija: [Pressure switch, electrical connection, type A](#)

Šifra: **103030RIE**

Kratek opis

Pressure switch, Electr. connection equipment plug A shape, Special die casting, Temperature -20 °C to 80 °C, G 1/4, 0.2 - 2 bar

For converting pneumatic to electrical signals.

Designed for use in rough vacuum applications (technical vacuum). Universal switch type, suitable as NC, NO or changeover contact. These devices are free from paint-wetting impairment substances (PWIS).

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Aplikacije	Pneumatic applications
Gumb za prilagajanje	Aluminium, powder-coated
IP zaščita	IP65 (DIN 43650), IP67 (M12x1)
Membrane	NBR
Ohišje	Special die-cast material
Povezava	G 1/4
Tesnilo	NBR
Min. prilagoditveno območje [bar]	0.2
Max. območje nastavitve [bar]	2
B [mm]	28.0
A [mm]	48.0
Max. temperaturno območje [°C]	80
Preklopna frekvenca	200/min.
Preklopna napetost	250 V AC / 28 V DC