

Datum: 23.05.2025



(slika je simbolična)

Varn krog. ventil ner.jeklo, z zaklepom, z izpustom, G 1

Kategorija: [Stainless steel safety ball valves lockable](#)

Šifra: **151734RIE**

Kratek opis

Stainless steel safety ball valve, lockable, Venting hole M5,
Operating temp. -20 °C to 160 °C, G 1, DN 25, PN max. 17
bar

Stainless steel safety ball valves.

Specially designed for pneumatic applications.

The ball valve can be locked manually and has a relief port.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Bore diameter padlock	ca. 7.8 mm
Izpušni vtič	M5
Krogelno tesnilo	PTFE + PFA
Krogla	Stainless steel 1.4408
Navoj	G 1
Ohišje	Stainless steel 1.4408
Opomba	The images maybe different from the original part
Ročica	Stainless steel 1.4301, PVC coated
Standardni navoj	G thread acc. to DIN EN ISO 228-1
Stebelno tesnilo	PTFE
Max. obratovalni tlak [bar]	17
C Ø [mm]	25.0
DN	25
B [mm]	69.3
L [mm]	88.7
A [mm]	145.0
Max. delovna temperatura [°C]	160