

Datum: 01.05.2025



(slika je simbolična)

## Varnostni krogelni ventil, z zaklepom, z izpustom, Rp 3/8

Kategorija: [Safety ball valves, lockable, with relief port](#)

Šifra: **103150RIE**

### Kratek opis

Safety ball valve, lockable, Venting hole M5, nickel-plated brass, Operating temp. -10 °C to 100 °C, Rp 3/8, DN 10, PN max. 14 bar

Safety ball valves, two parts, made of nickel-plated brass.

Specially designed for pneumatic applications.

The valve shuts off the supply line and bleds the application area.

Lockable hand lever in closed position ensures a high protection against manipulation.

### Tehnične Specifikacije

|                               |                            |
|-------------------------------|----------------------------|
| Min. delovna temperatura [°C] | -10                        |
| Bore diameter padlock         | ca. 7.3 mm                 |
| Izpušni vtič                  | M5                         |
| Krogelno tesnilo              | PTFE                       |
| Krogla                        | Chrome-plated brass        |
| Material navojev              | Nickel-plated brass        |
| Navoj                         | Rp 3/8                     |
| Ohišje                        | Nickel-plated brass        |
| Ročica                        | Steel - PVC coated         |
| Standardni navoj              | Rp thread acc. to EN 10226 |
| Stebelno tesnilo              | FKM                        |
| DN                            | 10                         |
| Max. obratovalni tlak [bar]   | 14                         |
| L [mm]                        | 45.0                       |
| B [mm]                        | 49.0                       |
| A [mm]                        | 96.0                       |
| Max. delovna temperatura [°C] | 100                        |