

Datum: 01.05.2025



(slika je simbolična)

## Visoko zmogl. varnos.ventil, G 1 1/4, vkl. prit. 0.6 bar

Kategorija: [High-pressure Varnostni ventil G 1 1/4](#)

Šifra: **116986RIE**

### Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260°C, G 1 1/4, AF 50, Trigger pressure 0.6 bar

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.

Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

### Tehnične Specifikacije

|                               |                                    |
|-------------------------------|------------------------------------|
| Navoj                         | G 1 1/4                            |
| Ohišje                        | Brass                              |
| Vzmet pokrova motorja         | Malleable iron, powder-coated blue |
| Min. obratovalni tlak [bar]   | 0.5                                |
| Min. nastavljeni tlak [bar]   | 0.6                                |
| A [mm]                        | 18.0                               |
| narediti [mm]                 | 25.0                               |
| Max. obratovalni tlak [bar]   | 30                                 |
| a/f [mm]                      | 50                                 |
| H [mm]                        | 231.0                              |
| Max. delovna temperatura [°C] | 260                                |