

Datum: 08.05.2025



(slika je simbolična)

## Visoko zmogl. varnos.ventil, G 1, vkl. prit. 11.5 bar

Kategorija: [High-pressure Varnostni ventil G 1](#)

Šifra: **105264RIE**

### Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 1, AF 41, Trigger pressure 11.5 bar  
Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.  
Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).  
Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

### Tehnične Specifikacije

|                               |       |
|-------------------------------|-------|
| Navoj                         | G 1   |
| Ohišje                        | Brass |
| Vzmet pokrova motorja         | Brass |
| Min. obratovalni tlak [bar]   | 0.5   |
| Min. nastavljeni tlak [bar]   | 11.5  |
| A [mm]                        | 16.0  |
| narediti [mm]                 | 20.0  |
| Max. obratovalni tlak [bar]   | 30    |
| a/f [mm]                      | 41    |
| H [mm]                        | 185.0 |
| Max. delovna temperatura [°C] | 260   |