

Datum: 01.05.2025



(slika je simbolična)

## Visoko zmogl. varnos.ventil, G 3/4, vkl. prit. 8.8 bar

Kategorija: [High-pressure Varnostni ventil G 3/4](#)

Šifra: **105181RIE**

### Kratek opis

High performance safety valve, Vibration-proof design, Brass, Operating temp. max. 260 °C, G 3/4, AF 36, Trigger pressure 8.8 bar

Proportional, spring-loaded safety valves with a lifting device. Type-tested acc. to VdTÜV Specification for safety valves 100.

Exceptionally reliable, even when installed in extreme environments (vibration-resistant design).

Suitable for compressed air and other non-toxic, neutral and non-flammable gases that may be freely released. Not suitable for steam.

### Tehnične Specifikacije

|                               |       |
|-------------------------------|-------|
| Navoj                         | G 3/4 |
| Ohišje                        | Brass |
| Vzmet pokrova motorja         | Brass |
| Min. obratovalni tlak [bar]   | 0.5   |
| Min. nastavljeni tlak [bar]   | 8.8   |
| A [mm]                        | 15.0  |
| narediti [mm]                 | 15.0  |
| Max. obratovalni tlak [bar]   | 30    |
| a/f [mm]                      | 36    |
| H [mm]                        | 153.0 |
| Max. delovna temperatura [°C] | 260   |