

Datum: 07.05.2025



(slika je simbolična)

Vrtljivi sesalni priključek »flexolink« G 1/4 IT, M10x1.25 ET

Kategorija: [Flexible suction pad mountings](#)

Šifra: **108545RIE**

Kratek opis

Pivoting suction pad attachment »flexolink«, G 1/4 IT, M10x1.25 ET, Steel / rubber, Bracket 12°, Bending moment 8 N

Flexible suction pad mounting

By flexing in all directions, this mounting allows the suction pad to better adapt itself to sloping workpieces.

Advantages:

- Very good adaptation to sloping workpiece surfaces
- Automatically resets into the initial position
- Vacuum-tight design with integrated protection against damage

Applications:

- Handling workpieces with sloping surfaces using large-area suction pads
- Handling large sheets of materials that may sag when lifted
- Can be used together with spring plungers to compensate for differing workpiece heights and uneven surfaces

Tehnične Specifikacije

Material	Steel, rubber
Navoj 1	G 1/4 IT
Navoj 2	M10x1.25 ET
L2 [mm]	8.0
Upogibni moment [N]	8
L1 [mm]	10.5
Kot [°]	12
a/f [mm]	17
Teža [g]	26.0
H [mm]	27.0
Vertikalna obremenitev [N]	500