

Datum: 30.04.2025



(slika je simbolična)

## Vtični-L fitting Click-klak, vrt., G 1/4 , cev Ø6

Kategorija: [Banjo elbow with inner hex, swivel type](#)

Šifra: **108641RIE**

### Kratek opis

Push-in L-fitting »click-clock«, rotating, G 1/4 o., for hose exterior Ø 6, Working pressure -0.99 to 16 bar, nickel-plated brass

The advanced version of our highly successful push-in fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.99               |
| Material                      | Nickel-plated brass |
| Navoj                         | G 1/4               |
| Priporočena cev               | PA, PU              |
| Rokav                         | Hostaform           |
| Serijska                      | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| a/f [mm]                      | 4                   |
| Za cevi O.D. [mm]             | 6                   |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 24.5                |
| L2 [mm]                       | 29.4                |
| Max. delovna temperatura [°C] | 80                  |