

Datum: 08.05.2025



(slika je simbolična)

## Vtični-L fitting Metallice vrt., G 1/2 , cev Ø 12

Kategorija: [Male elbow, swivel type, parallel ET with O-ring](#)

Šifra: **108908RIE**

### Kratek opis

Push-in L-fitting »metallica«, rotating, G 1/2 o., for hose exterior Ø 12, Working pressure -0.98 to 16 bar, nickel-plated brass

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

### Tehnične Specifikacije

|                               |                                                                 |
|-------------------------------|-----------------------------------------------------------------|
| Min. delovna temperatura [°C] | -20                                                             |
| Min. delovni tlak [bar]       | -0.98                                                           |
| Material                      | Nickel-plated brass                                             |
| Navoj                         | G 1/2                                                           |
| Priporočena cev               | PA and PU                                                       |
| Rokav                         | Nickel-plated brass                                             |
| Serijska                      | metallica                                                       |
| Vpenjalni obroč               | Male elbow, swivel type, parallel male thread with O-ring (FPM) |
| Za cevi O.D. [mm]             | 12                                                              |
| Max. delovni tlak [bar]       | 16                                                              |
| a/f [mm]                      | 20                                                              |
| L1 [mm]                       | 29.0                                                            |
| L2 [mm]                       | 35.0                                                            |
| Max. delovna temperatura [°C] | 150                                                             |