

Datum: 24.05.2025

Davčna št.: SI 56119488

Telefon: 01 500 14 42

E-mail: info@podjetje-trg.si

WWW: www.mail.karchertest.staging.digitalist.si



(slika je simbolična)

Vtični T-prik., L-oblika vrt. G 1/4 zunanje Ø6

Kategorija: [Male branch tee, angled plug connections](#)

Šifra: **135214RIE**

Kratek opis

Push-in T-fitting, L-shape, rotating, G 1/4 o., for hose exterior Ø 6 mm, Working pressure -0.98 - 20 bar, 1.4404 For use in more aggressive environments and corrosive media.

The suitability test for the individual application is the user's responsibility.

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. temperatura medija [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Stainless steel 1.4404
Navoj	G 1/4
Primerni materiali za cevi	PVDF, PTFE, PA, PU
Standardni navoj	DIN EN ISO 228-1
Tesnilo	FPM
Za cevi O.D. [mm]	6
a/f [mm]	17
Max. delovni tlak [bar]	20
L1 [mm]	22.1
L2 [mm]	50.1
Max. delovna temperatura [°C]	150
Max. temperatura medija [°C]	150