

Datum: 01.05.2025



(slika je simbolična)

Zaščitna spojka s tipko s prekr.maticol.D.6,ISO6150C,cev10x8

Kategorija: [Pushbutton safety coupl. DN6, male, hose connector](#)

Šifra: **141939RIE**

Kratek opis

Pushbutton safety coupling I.D. 6, ISO 6150 C, Stainless steel, Hose 10x8, Operating pressure max. 12 bar, Temp. -20 °C to 200 °C

"
High quality, robust and long-lifetime quick connect coupling in a safety design that can be operated with one hand. When pushed for the first time the coupling is vented, the plug remains securely in the coupling. After a second push the plug is released. This prevents a potential ""whiplash effect"" and the risk of operating personnel is practically excluded. The safety version meets ISO standard DIN EN ISO 4414. Areas of application: Pneumatic system, machine and plant engineering, measurement, monitoring and control systems, manufacturing industry, workshops, automotive, mining, offshore.
"

Tehnične Specifikacije

Min. temperaturno območje [°C]	-20
Gumb	Stainless steel
Merjenje pretoka	at 6 bar and $\Delta p = 1$ bar
Navojni kos	Galvanised steel
Ohišje	Stainless steel
Povezava	Hose connection 10x8
Tesnilo	FKM
Ventil	Brass
Vtični profil	acc. ISO 6150 C
Vzmet	Stainless steel
DN	6
Max. obratovalni tlak [bar]	12
a/f [mm]	20
Dolžina [mm]	62.0
Max. temperaturno območje [°C]	200
Pretok	1150 l/min (air)